

Oak In V01.20 January 2010

Originally authored by Toradex AG. This work is now available under the terms and conditions of the Creative Commons License 'Attribution CC BY'

Details of which can be found here: <http://creativecommons.org/licenses/by/3.0/>

1. Overview, Statistics

1.1. PCB

PCB type	rigid
Insulator material	FR4
Board Size Extents	48 X 48 mm (final size)
Layer Count	2
Board thickness	1.6mm
Copper thickness	35µm
Hole Count	77
Solder mask	on both sides
Silkscreen	no
Surface	HAL Pb-free

1.2. Statistics

Through Holes	71
Minimum line width	0.15mm
Smallest drill diameter	0.3mm
Smallest annular ring	0.15mm
Minimum spacing	0.15mm



1.3. Assembly

Assembly sides:	SMD and THT components on top side
SMD component count	56
THT component count	4
Pin Count	273

2. Layer Stackup

2.1. Sequence of the Gerber Files

Please stack the layers in the order given below:

File name	Description	Format
SoldermaskTop.gdo	<i>Solder mask (component side)</i>	RS274-X
EtchLayer1Top.gdo	top layer / component side	
EtchLayer2Bottom.gdo	bottom layer / solder side	RS274-X
SoldermaskBottom.gdo	<i>Solder mask (solder side)</i>	

2.2. Additional Files

SolderPasteTop.gdo	Solder Paste (component side)	RS274-X
Mechanics.gdo	Mechanical dimensions	RS274-X
ThruHoleNonPlated.ncd	Drill coordinates (plated)	NC drill
ThruHolePlated.ncd	Drill coordinates (non-plated)	NC drill
ContourPlated.ncd	Milling coordinates (non-plated)	NC drill

2.3. Layer thickness

The total thickness of the board must be 1.7mm±0.1mm

Proposed thicknesses:

	Description	Material	Thickness
	Top Solder Mask		
1	Top Layer	Cu	35u
		Core	1600u
4	Bottom Layer	Cu	35u
	Bottom Solder Mask		
Overall thickness			1.7mm



Disclaimer:

Copyright © Toradex AG. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies.

Brand and product names are trademarks or registered trademarks of their respective owners.

Specifications are subject to change without notice.